

Wheel Alignment M/C

AG400

Extensive Functions:

- Steering Wheel Aligning
- Body Measurement
- Vehicle Lift Measurement
- Engine Bracket Adjustment
- Toe-In Lockup Measurement
- Toe-In Curvature Measurement
- Single Wheel Measurement
- Inspection of Height Level
- Axis Deviation Measurement
- Wheel Deviation Measurement
- Zero Toe-in Camber Measurement
- Axis Distance Measurement
- Scrub Radius Measurement
- Wheel Distance Measurement



Technical Specifications:

Camera min 5 m pixel, international famous brand camera, high accuracy, more stable and reliable can be used longer than 8 years

Automatic tracking cameras, the beam can move and adjust the height according to the height of the target plates automatically

Double screens, more convenient for operator's checking

3-point clamp is with rim protection arm hooks and nylon covers,

Wheel clamps : diameter13-26 mm

Target: Front target 120 mm x140 mm

Screen :Dual 32inch and 19 inch

All targets are with water and oil proof and with patent technology

Over/Low voltage protectors will self-check real voltage status for 50s after power on. If the voltage is safe, then the computer can be turned on.

Power: 220v

Display accuracy: 1/0.1mm, Measurement Range: 1/0.1mm

Camber accuracy: ± 2 , Measurement Range: $\pm 10^\circ$

Caster accuracy: ± 6 , Measurement Range: $\pm 20^\circ$

Kingpin Inclination accuracy: ± 6 , Measurement Range: $\pm 23^\circ$

Toe-in & toe-out accuracy: ± 2 , Measurement Range: $\pm 20^\circ$

Set back accuracy: ± 2 , Measurement Range: $\pm 5^\circ$

Thrust angle accuracy: ± 2 , Measurement Range: $\pm 5^\circ$

Wheel deviation accuracy: ± 2 mm

Axis deviation accuracy: ± 2 mm