

## Guangdong Zhongcai Education Equipment Co.,Ltd

Add: #314, No.3 building, Mingjie kechuang Center, Beitai Road, 1633, Baiyun district, Gaungzhou, china.

Tel: 0086-20-36559771, Mob/whatsapp: 0086-13054484532

Wechat: 0086-13054484532 E-mail: biz.m@gdzcee.com

Web:www.zcequipment.com & www.gdzcee.com



## Tyre Changer Model: ZC-QC006D

## Specification:

Taller vertical post with dismounting max. tire width of 300mm  Universal switch with 40A silver contact for durability  Hexangular shaft made of S41mm steel material to avoid distortion  The foot pedal assembly punched from high quality steel material for durability  Clamps should be casted by fine alloy steel  Dismounting head should be made of special steel  Working Speed  6rpm  Tire diameter  1000mm  Outside Clamping  9" ~ 21"  Inside Clamping  13" ~ 25"  Tire width  3-14?  Working pressure		
Hexangular shaft made of S41mm steel material to avoid distortion  The foot pedal assembly punched from high quality steel material for durability  Clamps should be casted by fine alloy steel  Dismounting head should be made of special steel  Working Speed 6rpm  Tire diameter 1000mm  Outside Clamping 9" $\sim 21$ "  Inside Clamping 13" $\sim 25$ "  Tire width 3-14?	Taller vertical post with dismounting max. tire width of 300mm	
The foot pedal assembly punched from high quality steel material for durability  Clamps should be casted by fine alloy steel  Dismounting head should be made of special steel  Working Speed 6rpm  Tire diameter 1000mm  Outside Clamping 9" $\sim 21$ "  Inside Clamping 13" $\sim 25$ "  Tire width 3-14?	Universal switch with 40A silver contact for durability	
Clamps should be casted by fine alloy steelDismounting head should be made of special steelWorking Speed6rpmTire diameter $1000 \text{mm}$ Outside Clamping $9" \sim 21"$ Inside Clamping $13" \sim 25"$ Tire width $3-14?$	Hexangular shaft made of S41mm steel material to avoid distortion	
Dismounting head should be made of special steelWorking Speed6rpmTire diameter $1000mm$ Outside Clamping $9" \sim 21"$ Inside Clamping $13" \sim 25"$ Tire width $3-14?$	The foot pedal assembly punched from high quality steel material for durability	
Working Speed6rpmTire diameter $1000 \text{mm}$ Outside Clamping $9" \sim 21"$ Inside Clamping $13" \sim 25"$ Tire width $3-14?$	Clamps should be casted by fine alloy steel	
Tire diameter $1000 \text{mm}$ Outside Clamping $9" \sim 21"$ Inside Clamping $13" \sim 25"$ Tire width $3-14?$	Dismounting head should be made of special steel	
Outside Clamping $9" \sim 21"$ Inside Clamping $13" \sim 25"$ Tire width $3-14?$	Working Speed	бгрт
Inside Clamping 13" ~ 25" Tire width 3-14?	Tire diameter	1000mm
Tire width 3-14?	Outside Clamping	9" ~ 21"
	Inside Clamping	13" ~ 25"
Working pressure 8 ~ 10bar	Tire width	3-14?
	Working pressure	8 ~ 10bar
Power source 220~230V AC, 50Hz, 1 Phase	Power source	220~230V AC, 50Hz, 1 Phase