



Wheel Balancing M/C Model: ZC-QC020D

Features:

- 19 inch LCD display, 3D animation interface
- Multiple balancing modes: Static balancing and dynamic balancing procedures, four types ALU balancing mode and ALU-S mode
- High-precision main shaft with heat treatment process with troubleshooting and self-calibration function
- HTD function, split balance weight to back of tyre can protect outside of rim from damage
- OPT function, wheel and rim optimization
- Foot brake positioning at unbalanced point, improve the balancing accuracy
- Motor brake positioning at unbalanced point, more accurate and convenient
- Laser Positioning function

Specification:

Voltage	220V
Power	0.20 kw



Guangdong Zhongcai Education Equipment Co.,Ltd

Add: #314, No.3 building, Mingjie kechuang Center, Beitai Road, 1633, Baiyun district, Gaungzhou, china.

Tel: 0086-20-36559771, Mob/whatsapp: 0086-13054484532

Wechat: 0086-13054484532

E-mail: biz.m@gdzcee.com

Web:www.zcequipment.com & www.gdzcee.com

Balance Speed	180 rpm
Balance Cycle	7s
Wheel width	1.5-16??
Rim diameter	10-24?
Wheel diameter	999 mm
Sample Balancing weight STD	5gm, 15 gm, Ad chive 15 or 20 Bar